

**SEMICONDUCTOR ELEMENT PICKUP DEVICE**

PAJ 00-79-76 02098157 JP NDN- 190-0036-4453-5

**INVENTOR(S)-** ATSUYA, ARAKAWA

**PATENT APPLICATION NUMBER-** 63250385

**DATE FILED-** 1988-10-04

**PUBLICATION NUMBER-** 02098157 JP

**DOCUMENT TYPE-** A

**PUBLICATION DATE-** 1990-04-10

**INTERNATIONAL PATENT CLASS-** H01L02168

**APPLICANT(S)-** MATSUSHITA ELECTRON CORP

**PUBLICATION COUNTRY-** Japan

**PURPOSE:** To minimize a damage to be applied to a semiconductor element by lifting the element adhering to an adhesive sheet by dividing by means of a needle, and providing a drive source for vertically moving the lifting needle separately from a drive source for a pickup tool when picking up it.

**CONSTITUTION:** A semiconductor element 2 adhering onto an adhesive sheet 1 by dividing is lifted upward by a lifting needle 4 driven by a first drive source 3 to facilitate the pickup of the element 2. Then, a second drive source 5 is operated in synchronization therewith, it is attracted by a pickup tool 6 and conveyed. The source 3 is controlled by a numerical controller 7. Thus, the element 2 is separately lifted and picked up by the drive sources, the moving distance and speed of the needle 4 are freely set, and the condition of stably picking it can be easily set.

**COPYRIGHT:** (C)1990,JPO&Japio